

Categories

Work Desk

A.1. Work Surface

A.1.1. The work surface is manufactured from **E0.5-class melamine**, with a thickness of **18 mm**, and features **2 mm-thick ABS** edge banding around its perimeter.

A.2. Frame

A.2.1. The desk work surfaces are supported by a frame made of **rectangular-section steel profiles measuring 20 × 40 × 2 mm**.

A.2.2. The desk supports have a cross-section of **45 × 45 × 2 mm externally** and **40 × 40 × 2 mm internally** for the height-adjustable desks.

A.2.3. The height of the desks can be adjusted in **10 mm increments**, within a range of **650 to 850 mm**.

A.2.4. All desk types are equipped with **levelling adjusters**, with a levelling adjustment range of **0 to 25 mm**.

A.2.5. The desks are assembled and disassembled using only **four (4) bolts**, with **concealed tightening through a cast aluminium joint**. This specific construction solution is **patented by DROMEAS**.

A.2.6. All desk types are provided with provisions for:

- **Computer holder/base support**
- **Installation of a vertical front panel (modesty panel)**
- **Installation of a cable management channel**
- **Installation of sound-absorbing partition panels.**

A.2.7. The steel frame is finished with **electrostatic powder coating**.

A.2.8. The desks can easily be **adapted to the changing needs of the user**. They can be configured into **double or four-person workstations**, using concealed connectors to join two or more desks.

Product Certificates:

RAL-UZ 38 – Environmental criteria for office furniture

