

Categories

Work Desk

A.1.1. All desks feature a **support frame made of painted steel tubing with a diameter of 40 mm and a thickness of 1.5 mm.**

A.1.2. The vertical supports are internally manufactured from **steel tubing with a diameter of 40 mm and a thickness of 1.5 mm**, which is externally clad with **beech wood**.

A.1.3. The connecting joints between the vertical and horizontal frame elements are manufactured from **die-cast aluminium**, finished with **electrostatic powder coating**.

A.1.4. The work surfaces have a **thickness of 18 mm** and are manufactured from **three-layer E0.5-class particleboard**, with melamine coating on both sides and **2 mm-thick edge banding** around the perimeter.

A.1.5. All desk types are equipped with **levelling adjusters**, with an adjustment range of **0 to 25 mm**.

A.1.6. All desk types can be fitted with **18 mm-thick modesty panels**, manufactured from **E0.5-class particleboard with melamine coating**, as well as **cable management channels and cable outlet grommets**.

A.1.7. The **dimensions, shapes and colours of the work surfaces** are specified according to the **DROMEAS price list**.

Products Certifications:

DE-UZ 38 – (Blauer Engel) – Low-Emission Furniture and Slatted Frames Made of Wood and Wood-Based Materials



Bl. Industrial area of Serres, 62 121 P.: +30 23210 99220 / e-mail: dromeas@dromeas.gr / www.dromeas.com