

Categories

A. Floor-Mounted Partition Screens

- A.1.1.** The floor-mounted partition screens consist of a perimeter frame manufactured from rectangular aluminium profiles and are supported by heavy-duty steel base feet.
- A.1.2.** They are available in heights of **1100, 1300 and 1600 mm** and can be interconnected in straight-line configurations, as well as in **T-shaped** and **cross (+)** arrangements.
- A.1.3.** All frames incorporate an internal channel designed to accommodate dedicated aluminium profiles, allowing the installation of desk accessories as well as cable management channels.
- A.1.4.** The perimeter aluminium profiles are supplied with a natural anodised finish.
- A.1.5.** The floor-mounted partition screens can be fitted with infill panels made from the following materials:
- **E0.5** melamine-faced particleboard,
 - Clear tempered safety glass or chemically frosted tempered safety glass,
 - **E0.5** fabric-upholstered particleboard,
 - **12 mm PET acoustic panel.**
- A.1.6.** The overall height of the partition screens can be increased by means of an independent extension frame, connected to the main frame through specially designed die-cast aluminium connectors.

PRODUCT CERTIFICATIONS

- **EN ISO 354** – *Acoustics – Measurement of sound absorption in a reverberation room.*



B. Desk-Mounted Partition Screens

- B.1.1.** The desk-mounted partition screens are available in heights of **350 mm** and **450 mm** and are securely fixed to the desktop by means of specially designed die-cast aluminium connectors, ensuring safe and stable installation.
- B.1.2.** They can be interconnected in straight-line configurations, as well as in **T-shaped** and **cross (+)** arrangements.
- B.1.3.** All frames incorporate an internal channel designed to accommodate dedicated aluminium profiles, allowing the installation of desk accessories, such as monitor arms, as well as other functional accessories.
- B.1.4.** The perimeter aluminium profiles are supplied with a natural anodised finish.
- B.1.5.** The desk-mounted partition screens can be fitted with infill panels made from the following materials:
- **E0.5** melamine-faced particleboard,
 - Clear tempered safety glass or chemically frosted tempered safety glass,
 - **E0.5** fabric-upholstered particleboard,
 - **12 mm PET acoustic panel.**
- B.1.6.** The overall height of the desk-mounted partition screens can be increased by means of an independent extension frame, connected to the main frame through specially designed die-cast aluminium connectors.

Product Certifications:

- **EN ISO 354** – *Acoustics – Measurement of sound absorption in a reverberation room.*

