

## Categories

### Auxiliary Desk

#### A.1. Four-star base for Ø600 and Ø800 round tables

**A.1.1.** The worktop is connected to the central leg by means of a **5 mm-thick steel disc**. In the case of a **transparent glass worktop**, a specially machined **aluminium connector** is used.

**A.1.2.** The vertical support for round tables with diameters of **Ø600 mm and Ø800 mm** is manufactured from either **stainless steel (INOX)** tubing or **electrostatically powder-coated steel** tubing, with a diameter of **40 mm and a thickness of 1.5 mm**.

**A.1.3.** The base is a **four-star base**, manufactured from **polished die-cast aluminium**, and is fitted with special glides. For round tables with diameters of **Ø600 mm and Ø800 mm**, the diameter of the four-star base is **Ø671 mm**.

#### A.2. INOX and painted base for Ø1000 and Ø1200 round tables

**A.2.1.** The worktop is connected to the central leg by means of a **5 mm-thick steel disc**. In the case of a **transparent glass worktop**, a specially machined **aluminium connector** is used.

**A.2.2.** The vertical support for round tables with diameters of **Ø1000 mm and Ø1200 mm** is manufactured from either **stainless steel (INOX)** tubing or **electrostatically powder-coated steel** tubing, with a diameter of **60 mm and a thickness of 2 mm**.

**A.2.3.** The base is manufactured from **8 mm-thick steel sheet**, onto which a decorative disc is fitted. For round tables with a diameter of **Ø1000 mm**, the base has a diameter of **600 mm**, while for round tables with a diameter of **Ø1200 mm**, the base has a diameter of **800 mm**.

**A.2.4.** In the case of the **INOX base**, the decorative disc is manufactured from **1 mm-thick stainless steel sheet**. In the case of the painted base, the decorative disc is manufactured from **1 mm-thick steel sheet**, finished with **electrostatic powder coating**.

## B. Worktops

**B.1.** The round tables are available with the following worktop options:

- **Extra-clear tempered (Securit) glass worktop**, with a thickness of **10 mm** for round tables with diameters of **Ø1200 mm** and **Ø1000 mm**, and **8 mm** for round tables with diameters of **Ø800 mm** and **Ø600 mm**.
- **Melamine-faced particleboard worktop**, with a thickness of **18 mm**.
- **Wood veneer-faced particleboard worktop**, with a thickness of **25 mm**.

### Product Certificates:

**RAL-UZ 38** – Environmental label for **electrically height-adjustable desks**.

